

iWL Series

Bring compact, reliable wireless mobility to the point of sale

- Optimize revenue opportunities with 24/7 wireless connectivity.
- Reinvent mobile payment using a compact-sized device with a long-life battery and fast printer.
- Bring wireless mobile payment to your point of sale (POS).
- Discover a wide range of POS solutions for small merchants, hospitality and mobile businesses.

















Highest Security

The iWL Series meets the highest security requirements and is PCI PTS 2.x and 3.x certified with SRED & Open protocol modules.

All Payment Options

The iWL Series accepts EMV chip & PIN, magstripe and NFC/contactless, as well as enables new NFC couponing and e-wallets.

Compact-Sized

The compact iWL Series is a small and light electronic payment device.

Designed for Mobility

Designed specifically for mobility, the iWL Series provides extended battery life, in a lightweight, robust, compact-sized design and features a wide backlit keypad for outstanding display readability inside or outdoors.

Long Battery Life

Anticipating active use in remote environments, Ingenico Group focused on delivering outstanding battery life. In most cases, the iWL Series is designed to run all day in the most active retail environments.

All Wireless Connectivity

Featuring a complete portfolio with multiple wireless connectivity options – GPRS, 3G, Wi-Fi & Bluetooth Class 1– the iWL Series delivers enhanced network quality of service. Smooth integration of the iWL Series into multi-device solutions is ensured.

Outstanding Printer

The iWL Series 30-lines-per-second printer is one of the fastest on the market, for on-the-spot checkout efficiency.

Telium 2 Advanced

Powered by the Ingenico Group, Telium 2 technology is the result of 30 years' experience in the payment industry. Secure, highly integrated and fast, Telium 2 is the world's best platform to provide payment services with a library of over 2,000 applications. Telium 2 is a fully scalable, reliable operating system embedded into Ingenico Group's 27 million terminals deployed worldwide.









iWL Series			iWL 220	iWL 250
Processor		ARM 9 & ARM 7	•	•
Memory		16 RAM/16 Flash	•	N/A
		32 RAM/128 Flash	Option	•
		Micro-SD reader	•	•
SAM			2	2
Card Readers		Smart card	1	1
		Magstripe	•	•
		Contactless	•	•
Display			FSTN Monochrome graphic 128 x 64 pixels White backlit 2.53"	Transmissive TFT-LCD Color QVGA 320 x 240 pixels 4096 colors 2.81"
Terminal connectivity	Wireless	WAN LAN Multicom	Bluetooth Wi-Fi	3G/GPRS Bluetooth Wi-Fi
	Wired		Micro USB type A/B (host & slave)	Micro USB type A/B (host & slave)
Keypad		Backlit operational keys	15	15
		Navigation keys	7	7
Audio		Buzzer	•	•
		Speaker	Option	Option
Thermal printer		Speed in lines/second	30 l/s	30 l/s
Power supply		Terminal/base	5V 1A	5V 1A
		Terminal car charger	5V 0.75A - option	5V 0.75A - option
Batteries		Li-lon	2200 mAh	2200 mAh
Terminal size		LxWxH (Paper roll cage 0.98") (Paper roll cage 1.57")	5.90"x3.07"x1.73" 6.49"x3.07"x2.12"	5.90"x3.07"x1.73" 6.49"x3.07"x2.12"
Weight			10.05 oz	10.05 oz
Customization		Lens marking Printer cover flap Top casing	Option Option Option	Option Option Option
Optional base		Charger	•	•
		RS232	2 (option)	2 (option)
		USB A	Option	Option
		USB B	Option	Option
		Modem	Option	Option
		Ethernet 10/100 Base T	Option	Option
		Bluetooth	Option	Option
Environment		Operating temperature Storage temperature Relative humidity, non condensing	14°F to 113°F -4°F to 131°F 85% HR at 104°F	14°F to 113°F -4°F to 131°F 85% HR at 104°F
Security		Online & offline	PCI PTS 2.x & 3.x certified	PCI PTS 2.x & 3.x certified





