HiStone

HS210R



Android Self Service Kiosk

The Histone HS210 can be configured as either a Self-Ordering System or a Self-Checkout System to suit your application needs flawlessly. The HS210 is a compact and cost-effective solution for smaller groceries, bodegas, delis, and more – where space and budget restrictions apply. Build the perfect solution by selecting your desired combination of optional accessories including, Stands, Base, Wall mount brackets or counter stands, product trays, scanners, EFT Brackets, transaction printer, and even facial recognition cameras!

- 21.5" LCD Screen with Projected Capacitive Touch (PCT)
- ARM RK3288 (4core) High Speed CPU
- Android 7.1 (Nougat) Operating System
- Tempered Glass Flat Front Panel
- · WiFi and Bluetooth Standard
- Optional Facial Recognition Camera
- Optional Integrated Thermal Receipt Printer
- Optional Integrated 2D Barcode Scanner
- Optional Electronic Payment Processing Terminal Bracket
- Durable Plastic or Stainless Steel Trays Available
- Supports Wall Mount or Optional Stand

Shown with optional base and stand, facial recognition camera, SNBC BTP-S80 thermal receipt printer, Honeywell 2D scanner and electronic payment processing terminal bracket. Use the payment processing terminal of your choice.



HS210R Android Self Service Kiosk

Standard Features

- 21.5" LCD Screen
- Ten-Point Capacitive Touch
- ARM RK3288 (4core) CPU
- Tempered Glass Flat Front Panel
- Integrated 5W Dual Speakers
- · WiFi and Bluetooth Standard
- Exceptional Cable Management

Options and Upgrades

Configure your system with these easy to add options:

- · Base and Stand Can Accommodate Two **HS210R Terminals**
- · Choice of Durable Plastic or Stainless Steel Small or Large Shelving Platforms
- Integrated SNBC BTP-S80 Thermal Receipt Printer
- 2D Honevwell Barcode Scanner
- Cube Printer / Scanner Housing
- Integrated Camera Facial Recognition Capable
- · Electronic Payment Processing Terminal **Bracket**
- Wall Mount Bracket

Connectivity

- COM1 / COM3 / COM5 = DB9M
- USB1 / USB2 / USB3 = V2.0

Specifications

Processor: ARM RK3288 (4core) Cores / Threads Dual Core / 4 Threads

Cache Memory: 512KB L2 Mass Storage Device: 16GB eMMC

RAM Memory (1 Slot): 2GB

Display LCD: Tempered True Flat 21.5" LCD with LED Backlighting

Ten-Point Capacitive Touch Touch:

1920 x 1080 Resolution:

Aspect Ratio: 16:9

Integrated Speakers: Two Integrated 5 Watt Speakers **Integrated Camera Option:** Camera - Facial Recognition Capable

Integrated Scanner Option: Honeywell 2D Scanner

Printer Option- Model/Size: SNBC BTP-S80 Thermal 80mm Printer

> Speed: 250mm per Second (10")

Communication - Ethernet: RJ45 Gigabit Standard

> WiFi: Dual Band WiFi 802.11a/b/n/ac 2.4GHz/5GHz

Bluetooth: BT4.0

Operating System: Android 7.1 (Nougat) **Operating Voltage:** 90 ~ 132 / 180 ~ 264VAC

Temperature -50° ~ 104° F Operating:

Storage: 23° ~ 122° F

Humidity -Operating: 30% ~ 75% RH (Non-Condensing)

Storage: 30% ~ 80% RH (Non-Condensing)

Dimensions -32-1/2"W x 66"H x 22-5/8"D (With Small Shelf) Overall:

Unit: 14-1/4"W x 31"H x 6"D (With Camera / Printer)

Base & Stand: 25-1/2"W 57-3/4"H x 22-5/8"D

Safety and EMI: FCC / CE



Choice of Optional Small or Large Shelving Platforms in Durable Plastic (Shown) or Stainless Steel

